









Three Phase String Inverter

SUN- 20K-G03



-  2 MPP trackers, Max. efficiency up to 98.6%
-  Zero export application, VSG application
-  String intelligent monitoring (optional)
-  Wide output voltage range
-  Anti-PID function (Optional)
-  Build in AFCI
-  Rapid Shutdown system (Optional)

Technical Data

Model	SUN-20K-G03
Input Side	
Max. DC Input Power (kW)	26
Max. DC Input Voltage (V)	1000
Start-up DC Input Voltage (V)	250
MPPT Operating Range (V)	200~850
Max. DC Input Current (A)	32+32
Max. Short Circuit Current (A)	48+48
Number of MPPT / Strings per MPPT	2/2
Output Side	
Rated Output Power (kW)	20
Max. Active Power (kW)	22
Nominal Output Voltage / Range (V)	3L/N/PE 380V/323V-418V, 400V/340V-440V
Rated Grid Frequency (Hz)	50 / 60 (Optional)
Operating Phase	Three phase
Rated AC Grid Output Current (A)	29
Max. AC Output Current (A)	31.9
Output Power Factor	0.8 leading to 0.8 lagging
Grid Current THD	<3%
DC Injection Current (mA)	<0.5%
Grid Frequency Range	47~52 or 57~62 (Optional)
Efficiency	
Max. Efficiency	98.6%
Euro Efficiency	97.8%
MPPT Efficiency	>99%
Protection	
DC Reverse-Polarity Protection	Yes
AC Short Circuit Protection	Yes
AC Output Overcurrent Protection	Yes
Output Overvoltage Protection	Yes
Insulation Resistance Protection	Yes
Ground Fault Monitoring	Yes
Anti-islanding Protection	Yes
Temperature Protection	Yes
Integrated DC Switch	Yes
Remote software upload	Yes
Remote change of operating parameters	Yes
Surge protection	DC Type II / AC Type II
General Data	
Size (mm)	330Wx508Hx206D
Weight (kg)	20.8
Topology	Transformerless
Internal Consumption	<1W (Night)
Running Temperature	-25~65°C, >45°C derating
Ingress Protection	IP65
Noise Emission (Typical)	<45 dB
Cooling Concept	Smart cooling
Max. Operating Altitude Without Derating	2000m
Designed Lifetime	>20 years
Grid Connection Standard	CEI 0-21, VDE-AR-N 4105, NRS 097, IEC 62116, IEC 61727, G99, G98, VDE 0126-1-1, RD 1699, C10-11
Operating Surroundings Humidity	0-100%
Safety EMC / Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2
Features	
DC Connection	MC-4 mateable
AC Connection	IP65 rated plug
Display	LCD1602
Interface	RS485/RS232/Wifi/LAN

PEA & MEA LIST

