






Three Phase String Inverter

SUN- 6 / 10 K-G03



-  2 MPPT trackers, Max. efficiency up to 98.3%
-  Zero export application, VSG application
-  String intelligent monitoring (optional)
-  Wide output voltage range
-  Anti-PID function (Optional)
-  Build in AFCI
-  Rapid Shutdown system (Optional)

Technical Data

Model	SUN-6K-G03	SUN-10K-G03
Input Side		
Max. DC Input Power (kW)	7.8	13
Max. DC Input Voltage (V)	1000	
Start-up DC Input Voltage (V)	140	
MPPT Operating Range (V)	120~850	
Max. DC Input Current (A)	13+13	
Max. Short Circuit Current (A)	19.5+19.5	
Number of MPPT / Strings per MPPT	2/1	
Output Side		
Rated Output Power (kW)	6	10
Max. Active Power (kW)	6.6	11
Nominal Output Voltage / Range (V)	3L/N/PE 380V/323V-418V, 400V/340V-440V	
Rated Grid Frequency (Hz)	50 / 60 (Optional)	
Operating Phase	Three phase	
Rated AC Grid Output Current (A)	8.7	14.5
Max. AC Output Current (A)	9.6	15.9
Output Power Factor	0.8 leading to 0.8 lagging	
Grid Current THD	<3%	
DC Injection Current (mA)	<0.5%	
Grid Frequency Range	47~52 or 57~62 (Optional)	
Efficiency		
Max. Efficiency	98.3%	
Euro Efficiency	97.5%	
MPPT Efficiency	>99%	
Protection		
DC Reverse-Polarity Protection	Yes	
AC Short Circuit Protection	Yes	
AC Output Overcurrent Protection	Yes	
Output Overvoltage Protection	Yes	
Insulation Resistance Protection	Yes	
Ground Fault Monitoring	Yes	
Anti-islanding Protection	Yes	
Temperature Protection	Yes	
Integrated DC Switch	Yes	
Remote software upload	Yes	
Remote change of operating parameters	Yes	
Surge protection	DC Type II / AC Type II	
General Data		
Size (mm)	330W×457H×185D	
Weight (kg)	10	
Topology	Transformerless	
Internal Consumption	<1W (Night)	
Running Temperature	-25~65°C, >45°C derating	
Ingress Protection	IP65	
Noise Emission (Typical)	<25 dB	
Cooling Concept	Natural cooling	
Max. Operating Altitude Without Derating	2000m	
Designed Lifetime	>20 years	
Grid Connection Standard	CEI 0-21, VDE-AR-N 4105, NRS 097, IEC 62116, IEC 61727, G99, G98, VDE 0126-1-1, RD 1699, C10-11	
Operating Surroundings Humidity	0-100%	
Safety EMC / Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2	
Features		
DC Connection	MC-4 mateable	
AC Connection	IP65 rated plug	
Display	LCD1602	
Interface	RS485/RS232/Wifi/LAN	

PEA & MEA LIST

